

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

H04N 7/173, H04J 3/16, H04L 12/56

(11) International Publication Number:

WO 97/34421

(43) International Publication Date: 18 September 1997 (18.09.97)

(21) International Application Number:

PCT/US97/03984

A1

(22) International Filing Date:

12 March 1997 (12.03.97)

(30) Priority Data:

08/616,071 14 March 1996 (14.03.96) US 08/684,243 19 July 1996 (19.07.96) 211 08/760,412 4 December 1996 (04.12.96) US

(71) Applicant (for all designated States except US): TERAYON CORPORATION [US/US]; 2952 Bunker Hill Lane, Santa Clara, CA 95054 (US).

(72) Inventors; and


- (75) Inventors/Applicants (for US only): FUHRMANN, Amir, Michael [US/US]; 444 Saratoga Avenue #15G, Santa Clara, CA 95050 (US). RAKIB, Selim, Shlomo [US/US]; 23057 Cricket Hill Road, Cupertino, CA 95014 (US). AZENKOT, Yehuda [US/US]; 19400 Sorenson Avenue #128, Cupertino, CA 95014 (US).
- (74) Agent: FISH, Ronald, Craig; Falk & Fish, 16590 Oak View Circle, Morgan Hill, CA 95037 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: DATA TRANSMISSION USING ATM OVER HYBRID FIBER COAX



(57) Abstract

A process for reducing the amount of overhead data in ATM cell header prior to transmission upstream and downstream on a hybrid fiber coax cable plant (1003) or other transmission media using SCDMA on at least the upstream path, with out loss of either IP or Ethernet addressing information. Optimized downstream communication is achieved by establishing a virtual link between each remote unit an a central unit using dedicated SCDMA spreading codes assigned only to that virtual link.